

N-50 ZINCOT HEAVY ZINC POWDERED ANTIRUST AGENT

NABAKEM®
Chemicals & Aerosol

ผงสังกะสีกันสนิมแบบกัลวาไนซ์

คุณสมบัติ

- ป้องกันสนิมได้อย่างสมบูรณ์ด้วยกระบวนการกัลวาไนซ์ (Galvanizing) ระหว่างผงสังกะสีและโลหะขึ้นงาน ส่วนประกอบหลักของน้ำยา ZINCOT N-50 คือ ผงสังกะสีบริสุทธิ์
- คุณภาพการติดแน่นดีเยี่ยม ด้วยส่วนผสมของน้ำยาประสานพิเศษ
- ทนความร้อน, สารเคมี, กรดและอัลคาไลด์ได้ดี ผิวที่เคลือบมีอายุมากกว่า 1 ปีที่อุณหภูมิ 250 c°

การใช้งาน

- งานเรือ : ใต้ท้องเรือ, ช่องระบายอากาศ, ตัวแลกเปลี่ยนความร้อน, ถังน้ำ, ปั๊ม และอุปกรณ์ต่างๆในเรือ
- งานสะพาน : สายเคเบิลสะพาน, น๊อต, เกลียวต่อต่างๆ และชิ้นส่วนจากการเชื่อม
- งานรถยนต์ : ท่อไอเสีย, ตัวถัง, ใต้ตัวถัง, ท่อเข้าถังน้ำมัน, บริเวณที่มีการเชื่อม และอุปกรณ์ช่วยจอดต่างๆ
- ระบบกำเนิดไฟฟ้าและไฟฟ้าแสงสว่าง : หอส่งกำลัง, อุปกรณ์กระจายเสียง, เสาอากาศ, เสาสูง และไฟถนน
- งานก่อสร้าง : ท่อไต้ดิน, ช็องอ, งานโครงสร้าง และงานรั้ว
- งานอื่นๆ : ถังน้ำมัน, ท่อแอร์, อุปกรณ์ในโรงงานปิโตรเคมี, โครงสร้างเหล็กกลางแจ้ง, อุปกรณ์การเกษตร, คันกันตกบนทางด่วน เป็นต้น

ข้อควรระวัง

- (สำหรับกระป๋องสเปรย์) อย่าใช้ใกล้เด็กเล็ก และ ระวังแรงดันสูงในการป้องกัน
- ไม่ใช้ใกล้ไฟ, เตาไฟ หรือบริเวณที่อุณหภูมิสูงเกิน 40 c°
- หากใช้ในห้องปิด ควรจัดให้มีการระบายอากาศที่ดี
- หากใช้หมดให้เจาะรูกระป๋อง ห้ามโยนกระป๋องเข้ากองไฟ
- ไม่ควรเก็บไว้ในที่ชื้น ไม่มีอากาศถ่ายเท
- การใช้งานอาจไม่สมบูรณ์หากใช้งานอุณหภูมิต่ำกว่า 5 c°

FEATURES

- Excellent anti-rust effects ZINCOT N-50 is a product using high-purity zinc grey particles based on zinc galvanizing and provides permanent anti-rust effects by electrochemical action between zinc grey and metal.
- Excellent adhesiveness. High-adhesion special binder enduring any shock and bend is used.
- Excellent heat resistance and chemical-resistance. It endures over one year at 250 c° and is highly resistant to acid and alkali.



USE

- Vessel : Bottom, ventilation duct, heat exchanger, water tank, drain pump, marine facilities of vessels
- Bridge : Rustproofing of pier, wire rope, foot, bolt, nut and welded part
- Vehicles : Muffler, body, underbody, fuel tank inlet, welded area of heavy equipment, parking facilities
- Generation and electric system: Transmission tower, broadcasting facility, antenna, steel tower, street light
- Construction : Pipes installed underground, elbow, steel structure, fence
- Others : pipeline of refinery plant, piping and opening tank of freezer and air conditioner manufacturer, rustproofing of machinery and equipment of chemical plant, outdoor steel structures, agricultural equipment and snowplow, welded portion of guardrails in expressway, etc.

CAUTIONS

- (Aerosol) Keep it away from your children. This flammable product uses high-pressure gas.
- Do not use it toward fire.
- Do not use near heater or stove.
- Do not use in the room using fire.
- Do not keep it in the place above 40 c°
- Provide ventilation to use it in the closed room.
- Do not throw it away into fire.
- Punch the can to throw it away.
- Do not keep it in the closed place.
- Spraying may not work well below 5 c°

Packing : Aerosol 420ml/can, 20cans/box,
Liquid 1kg./Pail, Liquid 4kg./Pail