

เกจวัดแรงดัน VENUS Regulator VENUS

TANAKA

คุณสมบัติ

เกจสำหรับงานทั่วไป ตัวเรือนทำจากทองเหลืองเกรดสูง ภายในมีตัวกรองผงโลหะหรือสิ่งแปลกปลอม สามารถถอดประกอบเพื่อซ่อมแซมบำรุงรักษาได้ หน้าปัดคู่แสดงระดับแรงดันเข้าและออก ในหน่วย kg/cm^2 และ psi

การใช้งาน

ใช้ได้ดีกับงานอุตสาหกรรมทุกประเภท ที่ต้องการวัดแรงดันในถังแก๊ส และปรับตั้งแรงดันใช้งาน

FEATURES

Medium duty Forged brass body for maximum strength.. Sintered metal inlet filter to trap impurities.
*Soldered joints, for easy maintenance. Easy to read dual scale gauges in kg/cm^2 or psi with virtually unbreakable screw-on lexan lens.

APPLICATIONS

Medium duty regulator can be used for all industrial applications. Ideal for jobs where the need to read "cylinder" and "working" pressure is required.

SPECIFICATIONS

Model	VENUS O2 / N2	VENUS AC / LPG
Applied Gas	Oxygen / Nitrogen	Acetylene / LPG
Inlet Pressure Gauge	0 - 250 kg/cm^2	0 - 25 kg/cm^2
Outlet Pressure Gauge	0 - 25 kg/cm^2	0 - 2 kg/cm^2
Maximum Inlet Pressure	150 kg/cm^2 or less	15.5 kg/cm^2 or less
Maximum Outlet Pressure	9.9 kg/cm^2 or less	1.0 kg/cm^2 or less
Inlet Connection	CGA540 / 580	CGA300 / 510
Outlet Connection	M16x1.5RH with 1/4" Hose nipple	M16x1.5LH with 1/4" Hose nipple
Approximate weight	1.0kg	



Venus Regulator-N2



Venus Regulator-OX



Venus Regulator-LPG



Venus Regulator-AC