



### Spec

- Range : 0~300S (Sealed gage)
- Output : DC 4~20mA
- Accuracy : ±0.5%F·S
- Total error : ±2.0%F·S
- Power : DC 11~30V
- Temperature Compensated: 0~50° C
- Operation Temperature: -20~80° C
- Sensor Type : Oil Fill Type
- Wetted Material : 304L&316L

20mA Output

Cable Color

Red : IN+

White : OUT+

Black : spare

Green : E-case

P51-300S-SI-0G-20mA  
300psi Sealed gage  
SI: R 1/8 (1/8 PT) female  
20mA: DC 4~20mA  
0G: 0.3M cable length

Sheet 2 of 3 ▲

客戶: GENTEC		客戶圖號:		
產品No: P51		DWG.NO: 06038B		
一般公差				
尺寸範圍	容許差	TSMC No: P51-300S-SI-0G-20mA		
0.5<D≤3	±0.1	CHD.BY-Chunk.Lin	DRN.BY- Sun JenCheng	
3<D≤6	±0.1			
6<D≤30	±0.2	DATE: 2018/01/11	MATERIAL: NA	
30<D≤120	±0.3	REV- 1	UNIT- MM	
120<D≤400	±0.5			SCALE- 1:1
400<D≤1000	±0.8			
ANGULAR	±0.5			

