

# WP18

## WP/SR-18 TORCH-USA

### Technical Data:

Water-Cooled Tig Welding Torch

Rating: 380A DC/270A AC @ 100% Duty Cycle

0.040"-5/32"/1.0mm-4.0mm Electrodes



No.	PART NUMBER	DESCRIPTION
	WP-18-12-R	WP-18 Water-Cooled Torch Power Cable 718-14LH 12'(3.6m)
	WP-18-25-R	WP-18 Water-Cooled Torch Power Cable 718-14LH 25'(7.6m)

No.	PART NUMBER	DESCRIPTION
A	Standard Series	
B	Stubby Series	
C	Stubby Gas Lens Series	
D	Gas Lens Series	
E	Large Gas Lens Series	
1	WP-18	Torch body
2	98W18	Back Cap 'O' Ring
3	57Y04	Short Back Cap
4	57Y05	Medium back cap
5	57Y02	Long back cap
6	H-200	Handle Smooth
6-1	H-200R	Handle Ribbed

No.	PART NUMBER	DESCRIPTION
7	BL-1	Switch Boot,Rubber
7-1	BL-1S	Switch Boot,Snap-on
8	SW-1	Switch Button Momentary Bulb
8-1	SW-1F	Switch Button Momentary Flat
9	40V64R	Rubber Power Cable 12.5'(3.6m)
	41V29R	Rubber Power Cable 25'(7.6m)
10	40V75R	Rubber Gas Hose 12.5'(3.6m)
	41V30R	Rubber Gas Hose 25'(7.6m)
11	40V74R	Rubber Water Hose 12.5'(3.6m)
	41V32R	Rubber Water Hose 25'(7.6m)
12	45V11	Power Cable Adapter
13	LDT-1820-L	Power Cable Connection 7/8-14 (L.H.) Water Cooled
14	LDTI-1820-WC	Power Cable Connection 7/8-14 (L.H.) Water Cooled(In Line)
15	WC-3-10	Cable Cover 3"x10' Nylon with Zipper
	WC-3-22	Cable Cover 3"x22' Nylon with Zipper
16	WC-3-10C	Cable Cover 3"x10' Canvas with Zipper
	WC-3-22C	Cable Cover 3"x22' Canvas with Zipper

